





NOTES: UNLESS OTHERWISE SPECIFIED

- DIMENSIONS ARE IN INCHES (MM).
 MACHINED SURFACES TO BE 63 µIN MAX.

- MACHINED SORT ACES TO BE 65 µIN MAX.
 DO NOT SCALE DRAWING.
 PART TO BE FREE OF BURRS AND SHARP EDGES.
 ALL MATERIAL TO BE CLEAN, DEGREASED AND FREE OF ALL IMPURITIES.
 ANY CHANGE MUST BE AUTHORIZED BY AN SC&R ENGINEER.

MATERIAL TYPE: 316 SS **VENDOR ID:**

REV	DATE	DESCRIPTION OF CHANGE			ECN	BY	APPR
REVISIONS							
SC Stainless Cable & Railing		XX ±.01 TOLERANCES UNLESS XXX ±.005 OTHERWISE ANGULAR ±0.5° SPECIFIED FRACTIONAL ±1/32	OF STAINLESS CABLE & RAILING AND IS PROTECTED UNDER COPYRIGHT LAW AS AN UNPUBLISHED WORK. IT MAY	Standoff Space	cer		SHEET
DRAWN BY: DATE: 2/12/2012 PROJECT:		EXPRESS WRITTEN PERMISSION FROM SC&R.	01-040-01			1 OF 1	